

# 4-Optical 24-Electric Gigabit Management POE Switch FW2224GP

## PRODUCT FEATURES

24 \* 10/100/1000Mbps RJ45 port (POE)+2 \* 10/100/1000Mbps RJ45 port (non POE)+2 \* Gigabit SFP port

FW2224GP is a full gigabit three-layer network management PoE switch, which can meet the PoE power supply requirements of WIFI AP, IP camera, WIFI bridge, IP phone and other types of equipment. The product adopts a new generation of high-performance hardware and software platform, provides flexible, cost-effective full gigabit access and uplink ports, supports three-layer routing protocols, complete security protection mechanisms, perfect ACL/QoS policies and rich VLAN functions, is easy to manage and maintain, and meets users' networking needs for easy management, high security and low cost of network equipment. It is suitable for network access, convergence Core multiple application scenarios.

- 6kv port lightning protection: the full port supports 6KV lightning protection, PSE short circuit protection, PoE overload, power over temperature protection, overvoltage protection, surge current protection and other protection features.
- Business processing capability: support 802.1Q VLAN, MAC VLAN, IP VLAN, and users can flexibly divide VLANs as required; It supports the quick departure mechanism and querier of Layer 2 multicast, and supports Layer 2 IPv4 static multicast and Layer 2 IPv6 static multicast.
- Security mechanism: provide port isolation in the same VLAN, DHCP Snooping, IP+MAC+port binding and other security features to further ensure user data security.
- Reliability protection: support STP, RSTP and MSTP protocols, eliminate the two-layer loop and realize link backup.
- POE power supply function: support 802.3af/at standard, built-in high-power power supply, meet the requirements of security monitoring, wireless coverage,

IP phone and other POE scenarios.

- Management and maintenance: support SNMP V1/V2/V3, and facilitate the management of equipment through the network management platform.



## PRODUCT DETAILS

Product Model	FW2224GP
Network Interface	<ul style="list-style-type: none"> <li>● 24 10/100/1000M RJ45 ports (POE)</li> <li>● 2 10/100/1000M RJ45 ports (non POE)</li> <li>● 4 gigabit SFP optical ports</li> <li>● 1 Console port</li> </ul>
Performance Specifications	<ul style="list-style-type: none"> <li>● MAC address table: 8K</li> <li>● Backplane bandwidth: 56Gbps</li> <li>● Packet forwarding rate: 41.7Mpps</li> <li>● Port cache: 4.1 Mb</li> <li>● Forwarding mode: store and forward</li> </ul>
Power Support	<ul style="list-style-type: none"> <li>● Maximum output power: 30W</li> <li>● Voltage input: 100-240V DC</li> <li>● Maximum power: 250W</li> </ul>

LED Indicator	<ul style="list-style-type: none"> <li>● 1 SYS indicator light</li> <li>● 1 Power indicator</li> <li>● 24 PoE indicators</li> <li>● 28 Link/Act indicators</li> </ul>
Environmental Specifications	<ul style="list-style-type: none"> <li>● Working temperature: 0-40 °C</li> <li>● Storage temperature: - 40-70 °C</li> <li>● Storage humidity: 5% - 90% (non condensing)</li> </ul>
Network Protocol	<ul style="list-style-type: none"> <li>● IEEE802.3、IEEE802.3i、IEEE802.3u、IEEE802.3ab、IEEE802.3z、IEEE802.3ad、IEEE802.3x、IEEE802.1p、IEEE802.1q、IEEE802.1d、IEEE802.1s、IEEE802.1w、IEEE802.3af、IEEE802.3at</li> </ul>
Management	<ul style="list-style-type: none"> <li>● L3</li> </ul>
Size (W*D*H)	<ul style="list-style-type: none"> <li>● 440*44*180mm</li> </ul>

## APPLICATION COLLOCATION

